

Transparency
and natural light

.....
new Colours
Collection
.....

Soltis

Horizon 86

Applications

Facade blinds, veranda and glass roof blinds, drop-arm awning, pergolas and canopies, roll-up valances and shade sails



■ Excellent transparency

Soltis Horizon 86 provides excellent outward visual contact to enjoy the view even when the awning is lowered. It proves its efficiency by blocking up to 93% of the heat in outdoor use.

■ Optimised natural light contribution

Soltis Horizon 86 promotes natural light intake. This is beneficial in terms of:

- energy savings by reducing the use of artificial lighting;
- the well-being, health and productivity of people in a professional or private environment.

■ Harmonised ranges

All the colours of Soltis Horizon 86 are coordinated with Soltis Perform 92 to:

- harmonises all the facades of a building;
- meets visual comfort needs according to each facade's orientation;
- adjusts thermal protection to save energy.

BLOCKS UP TO
93%
OF THE HEAT

ALLOWS NATURAL
LIGHT TRANSMISSION
OF UP TO
28%

Soltis Horizon 86 - 3 key properties



Dimensional stability
thanks to Preconstraint technology



Easy to clean




UV resistant




Soltis

Horizon 86




new Snow white 177 cm — 267 cm

86-50690




White 177 cm — 267 cm

86-2044




Champagne 177 cm — 267 cm

86-2175




Pepper 177 cm — 267 cm

86-2012




Sandy beige 177 cm — 267 cm

86-2135




new Brick 177 cm

86-51180




new Deep red 177 cm

86-51181




new Deep blue 177 cm

86-51182



new Aniseed 177 cm

86-2157



Moss green 177 cm

86-2158



Buttercup 177 cm

86-2166




Orange 177 cm

86-8204




Red 177 cm


86-8255




Boulder 177 cm — 267 cm 86-2171




Alu/White 177 cm — 267 cm 86-2051




Alu/Oat 177 cm — 267 cm 86-2046




Alu/Alu 177 cm — 267 cm 86-2048




Alu/Anthracite 177 cm 86-2068



Concrete 177 cm — 267 cm 86-2167



Beaten metal 177 cm — 267 cm 86-2045



Bronze 177 cm — 267 cm 86-2043



Anthracite 177 cm — 267 cm 86-2047



new Deep black 177 cm — 267 cm 86-51176

new Colours Collection

A range of colours to match every kind of project


The new Soltis Horizon 86 range features colours designed by our design office to complement the building's entire environment (joinery, openings and facades). The colours present tones that match the most common colours (RAL and NCS references).



Download
our RAL and NCS
colour correspondence

■ Tecnologia esclusiva Preconstraint®

This unique globally patented technology consists of maintaining the composite in bi-axial tension throughout the manufacturing cycle. This gives our materials outstanding performance allowing them to surpass market standards in terms of dimensional stability, mechanical strength, coating thickness and flatness.



High-tenacity polyester micro-yarn weave ①	Superior elongation and tear resistance
Coating under bi-axial constant tension in both warp and weft directions ②	No deformation during processing and use
Greater coating at the top of the yarns and dirt-resistant surface treatment ③	Superior aesthetic and mechanical durability
Exceptional flatness and thinness ④	Smooth finish easy to clean, space saving, easy rolling

■ Light and solar properties (according to EN 14501 standard)

	Width (in cm)	TS	RS	AS	TV n-h	EN13363-2* Glazing D			
						177	267	g_{tot}^e	g_{tot}^i
						86-2012	• •	18	27
86-2043	• •	15	11	74	15	0.07	0.28		
86-2044	• •	29	59	12	28	0.11	0.15		
86-2045	• •	16	29	55	16	0.08	0.23		
86-2046 A	• •	22	40	38	21	0.10	0.16		
86-2046 B	• •	22	55	23	21	0.09	0.20		
86-2047	• •	17	7	76	17	0.07	0.28		
86-2048	• •	19	39	42	19	0.09	0.20		
86-2051 A	• •	22	40	38	20	0.09	0.13		
86-2051 B	• •	22	60	18	20	0.09	0.20		
86-2068 A	•	17	31	52	17	0.08	0.23		
86-2068 B	•	17	7	76	17	0.09	0.28		
86-2135	• •	24	39	37	22	0.09	0.21		
new 86-2157	•	25	44	31	21	0.08	0.21		
86-2158	•	18	25	57	16	0.08	0.25		
86-2166	•	31	45	24	28	0.11	0.21		
86-2167	• •	17	14	69	17	0.07	0.26		
86-2171	• •	22	36	42	20	0.08	0.21		
86-2175	• •	30	57	13	28	0.11	0.16		
86-8204	•	29	41	30	21	0.10	0.23		
86-8255	•	21	24	55	14	0.07	0.27		
new 86-50690	• •	28	61	11	27	0.11	0.14		
new 86-51176	• •	14	5	81	14	0.07	0.29		
new 86-51180	•	17	24	59	15	0.07	0.26		
new 86-51181	•	18	14	68	16	0.08	0.28		
new 86-51182	•	18	23	59	15	0.07	0.27		

A : Aluminium surface exposed to the sun
B : Coloured surface exposed to the sun
TS : Solar Transmission in %
RS : Solar Reflection in %
AS : Solar absorption in %
TS + RS + AS = 100% of the incident energy
TV n-h : Normal Visible light transmission - hemispherical in %
g_{tot}^e : External Solar Factor
g_{tot}^i : Indoor Solar Factor

*Detailed method
EN 52022-3

Takes into account the spectral values of glazing transmission and reflection + blind complex for calculating the solar factor g_{tot}^e .
Type "D" glazing: insulating double glazing with low emissivity on surface 2 (4 + 16 + 4; Argon filling) $g = 0.32 - U = 1.1$

Soltis

Horizon 86

	■ Technical properties	Standards
Openness factor	14%	
Weight	380 g/m ²	EN ISO 2286-2
Thickness	0.45 mm	
Width	177 cm - 267 cm	
■ Roll length		
Standard format: 177 cm	50 lm	
Standard format: 267 cm	40 lm	
■ Physical properties		
Breaking resistance (warp / weft)	230/160 daN/5 cm	EN ISO 1421
Tear resistance (warp / weft)	45/20 daN	DIN 53.363
■ Reaction to fire		
Rating	M1 /NFP 92-507 — B1 /DIN 4102-1 — BS 7837 — BS 5867 — Schwerbrennbar-Q1-Tr1 /ONORM A 3800-1 — Classe 1 /EN 13373 — M1 /UNE 23.727-90 — VKF 5.3 /SN 198898 — 1530.3/ AS /NZS G1 /GOST 30244-94 — Method 1 /NFPA 701 — CSFMT19 — Class A /ASTM E84	
Euroclass	B-s2.d0	EN 13501-1
■ Management system		
Quality	ISO 9001	

■ Certifications, labels, warranties

Précontraint®
Technology



bim
object®



5-year
warranty



■ Tools and services

- ACV and FDES available on request
- Personalised thermal performance simulation service for your projects and associated Soltis solar protection:
Get in touch with your Serge Ferrari contact

¹ "+=0" logo: summarises the Serge Ferrari Group's commitment to CSR, to align economic performance and positive impact.
Find out about our concrete actions in our CSR report 2021.

The technical characteristics provided are average values with a tolerance of +/- 5%.

Purchasers of our products are responsible for their application or transformation with regard to any third party rights. Purchasers of our products are also responsible for their implementation and installation in compliance with the destination country's best practices and safety rules. Contractual guarantees are included in the terms of the guarantee.

The values mentioned in this document are based on test results in compliance with study practice. These are provided as indications so that customers can obtain optimal performance from using our products. These are subject to technical improvements and we reserve the right to change specifications at any time. Purchasers of our products are responsible for asserting that the data presented above is in compliance with the validity of the above data.